

Signgrass® FitnessTracks

Textured Monofilament



Signgrass® FitnessTracks – Unique Branding, Custom or Standard Tracks

Discover Signgrass® FitnessTracks. Unique branding for your indoor or outdoor fitness space, we create standard or custom tracks according to your wishes.

Whether it's a standard design, or a custom design with logos, we work closely with our clients on each project to ensure a seamless fit with both function and design.

These fitness and sledtracks are made from high quality fiber and available in a large colour range. The textured fibre combined with a short pile height results in high definition, detailed images when adding that personal touch to your track. With a pile height ranging from 10 - 15 mm, customisable stitch rate, we are able to perfectly match the technical specifications of the surrounding artificial grass with endless possibilities for both infill and non-infill fields.

Tuft Characteristics

Pile Height	10 - 15 mm (margin \pm 2%)
Stitch Rate	250 - 350
Gauge	3/16"
Tuft Lock	2 kg



Yarn Characteristics

Type	Polyethylene Textured
Dtex	$8 \times 1100 = 8.800$

Possibilities

It's possible to supply us with your own yarn, under the condition a production test is permitted.

We require a technical datasheet and sample of the artificial grass.

There is no maximum size. Logo mats larger than 12 x 4 meters will consist out of multiple parts of which the joints need to be glued on location.

SIGNGRASS®
synthetic grass design

Stokskesweg 9B 5571 TJ Bergeijk The Netherlands

T +31 (0)497 5725 45 — E info@signgrass.com — I www.signgrass.com

Signrass® Short

Textured Monofilament

Backing Characteristics

Primary Backing	Polyethylene and Woven Polyester
Secondary Backing	Latex
Water Permeability	Drainage holes on request

Warranty

5 year warranty against discolouration and UV light degradation.

5 year product warranty against fibers coming off.

Total Product Weight

2500 g/sqm, depending on pile height and stitch rate.

Logo/Design

For the production of your logo or design, a Vector file is required. With preference .eps or .ai file.

Besides a square or rectangle mat, we can also tuft the shape of a logo or design like a circle, ellipse, hexagon or crest.

Margin total size logo mat $\pm 2\%$

Guidelines Logo/Design

Letters, signs and logos need to be legible and feasible, so please take following guidelines in account:

Product	Short 15 mm (3/16" gauge)
Minimum height letter	6 cm
Detail (Width)	0,8 cm
Space in between letters	0,8 cm

Installation & Maintenance

Our logo mats should only be installed by a professional in order to ensure the best result.

Seams have to be secured with polyurethane special adhesive for synthetic grass.

Signrass® logo mats are low in maintenance, just like artificial grass, but not maintenance-free!

- Brush the grass regularly with a stiff broom or rake
- Keep the grass free of debris and leaves
- Remove leaves using a leaf blower or rake
- Remove any weeds immediately to prevent seed dispersal
- Use clean water to rinse off any spills, such as liquids, sauce or melted ice-cream
- Pet excrement or smells can be removed using a shovel or detergent and water
- Avoid contact with hot materials (or close proximity to glass structures) to prevent shrinkage of the grass fibers.

Gas fading

The discolouring of polyethylene is a phenomenon that is well-known in polymer industry. It is also described as yellowing, pinking or gas fading. The colour changes of the material are generally a result of auto-oxidation of phenolic antioxidants in the basic polymer used. These phenolic antioxidants are added to the resin by the producer to protect and stabilize the polymer during processing and use. The change in colour of the polymer is strictly cosmetic and does not affect physical properties.

The sources of discolouration in polyethylene are diverse and can vary from packaging to inappropriate material composition. The most relevant source is excessive levels of atmospheric pollutants like nitrogen oxides (NOx). The relatively high levels of NOx are usually caused by exhaust gasses (gas fading), for example fork lift trucks and heaters in warehouses.

To reverse and remove the discolourations expose the material to UV-light (sunlight).

With respect to synthetic turf fibres, the yellow shine of white yarn will disappear after installation of an outside pitch. When using synthetic turf for an inside application, exposure to sunlight before installation will remove the yellow shine.

Signrass® Short

Standard colours available:

	T1 - white
	T17 - grey
	T19 - dark grey
	T2 - black
	T3 - yellow
	T4 - orange
	T5 - red
	T27 - claret red
	T14 - red clay
	T11 - brown
	T13 - cream
	T21 - gold
	T20 - lime green
	T9 - light green
	T10 - olive green
	T15 - dark green
	T30 - turquoise
	T26 - sky blue
	T7 - light blue
	T8 - dark blue
	T6 - purple
	T32 - fuchsia
	T12 - pink

Other colours on request.*